

# LISST-HAB

## HARMFUL ALGAE BLOOM (HAB) INSTRUMENT

- **Particle Size Distribution**
- **Volume Concentration**
  - **Phycocyanin**
  - **Phycoerythrin**
  - **Chlorophyll**
- **Beam Attenuation**

The LISST-HAB is a self-contained, stand-alone instrument system for use on profiling packages, towed and remote vehicle applications, for deployment during a HAB event. The system will continuously measure particle size distribution and concentration, along with the fluorescence of Phycocyanin, Phycoerythrin, Chlorophyll, and Beam Attenuation.



## FEATURES

- Complete package based on small angle forward scattering laser diffraction technology
- LISST-200X integrated with Turner Designs Cyclops-7F fluorometers
- Measures Phycocyanin, Phycoerythrin, Chlorophyll, particle size, concentration, beam attenuation, depth, temperature
- Self-Contained with internal programmable datalogger for autonomous data collection
- Externally powered (short- and long-term deployment battery packs included)
- USB connection to PC for programming, offloading and real-time size distribution displays
- Integrated depth and fast response temperature sensors
- Integrates on profiling package, tow vehicle or mooring/lander

### Fluorometer Performance

The Turner Designs submersible instrumentation modules used in the LISST-HAB includes single-channel fluorometers for detection of Phycocyanin, Phycoerythrin and Chlorophyll. Together with particle information from the LISST-200X, this package solution provides a comprehensive picture of cyanobacteria presence.

## SPECIFICATIONS (subject to change without notice)

### Parameters Measured

- Particle size distribution from 1  $\mu\text{m}$  – 500  $\mu\text{m}$  in 36 size ranges
- Depth @ 0.01 m resolution
- Temperature @ 0.01  $^{\circ}\text{C}$  resolution; response time 2.5 s
- Optical transmission @ 0.1 % resolution
- Volume Concentration @ 0.1  $\mu\text{L}\cdot\text{L}^{-1}$  resolution
- Beam attenuation
- Phycocyanin
- Phycoerythrin
- Chlorophyll

### Operating Concentration Range

- Optical transmission from 0.3 - 0.99 (30-99 %)
- Concentration from ~ 0.5 - 700  $\text{mg}\cdot\text{L}^{-1}$  (particle-size dependent)

	Minimum Detection	Linear Range
Phycocyanin	2 ppb <sup>PC</sup>	0-4,500 ppb <sup>PC</sup>
Phycoerythrin	0.1 ppb <sup>PE</sup>	0-750 ppb <sup>PE</sup>
Chlorophyll	0.03 $\mu\text{g}/\text{L}$	0-500 $\mu\text{g}/\text{L}$

### Technology (laser diffraction)

- Small-angle forward laser scattering
- 670 nm laser diode
- 32-ring custom photodiode Ring detector + 4 large angle detectors
- 25 mm optical path

### Mechanical and Electrical

- Dimensions [W × H × L]: 10.03 cm × 13.21 cm × 63.9 cm (3.95" × 5.2" × 25.2")
- Weight [air / water]: 6 kg / 2.5 kg (13.2 lbs / 5.5 lbs)
- Depth rating: 600 m
- External power input: 12 VDC nominal, 8 VDC to 24 VDC
- Current drain at 12 V: 100 mA Sampling, 8 mA between samples
- Sampling rate: Up to 1 Hz
- Data storage: 1 GB (~12,000,000 measurements; ~140 days @ 1 Hz)
- SubConn MCBH3M, MCBH5M and MCBH6M connectors
- Phycocyanin – optical filters: EX 590, EM  $\geq$  645
- Phycoerythrin – optical filters: EX 531, EM  $\geq$  590
- Chlorophyll – optical filters: EX 465, EM 496

